

**MK-dent PREMIUM SERVICE OIL (LU1011)**

Print date 06.10.2025

Revision date 06.10.2025

Version 1.2 (en)

replaces version of 10.11.2023 (1.1)



**MK-DENT**

---

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier**

Trade name/designation MK-dent PREMIUM SERVICE OIL (LU1011)

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

**Sector of uses [SU]**

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

**Use of the substance/mixture**

Lubricant

**1.3 Details of the supplier of the safety data sheet**

**Supplier**

MK-dent GmbH  
Marie-Curie-Straße 2  
D-22941 Bargteheide  
Telephone +49(0)4532-400490  
Telefax +49(0)4532-4004910  
E-mail info@mk-dent.com  
Website www.mk-dent.com

Department responsible for information:

Produktinformation / Product Information

Telephone +49(0)4532-400490

Telefax +49(0)4532-4004910

**1.4 Emergency telephone number**

Poison information centre Göttingen GIZ-Nord +49 (0) 551-19 240

(Advice in German and English)

---

**SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture**

Classification according to  
Regulation (EC) No 1272/2008  
[CLP]

Aerosol 1, H222

Aerosol 1, H229

Aquatic Chronic 2, H411

**Hazard statements for physical hazards**

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

**Hazard statements for environmental hazards**

H411 Toxic to aquatic life with long lasting effects.

**2.2 Label elements**

**Labelling according to Regulation (EC) No 1272/2008 [CLP]**

**MK-dent PREMIUM SERVICE OIL (LU1011)**

Print date 06.10.2025

Revision date 06.10.2025

Version 1.2 (en)

replaces version of 10.11.2023 (1.1)



**MK-DENT**

**Hazard pictograms**



GHS02



GHS09

**Signal word**

Danger

**Hazard statements**

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements**

P102 Keep out of reach of children.

P251 Do not pierce or burn, even after use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P391 Collect spillage.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Special rules for supplemental label elements for certain mixtures**

EUH208 Contains peppermint oil. May cause allergic reactions.

**2.3 Other hazards**

**Adverse human health effects and symptoms**

The mixture does not contain substances >=0.1% of substances that have endocrine disrupting properties according to Regulation (EC) No. 1907/2006, Article 59(1) or Regulation (EU) 2017/2100 or Regulation (EU) 2018/605.

**Adverse environmental effects**

The mixture does not contain substances >=0.1% of substances that have endocrine disrupting properties according to Regulation (EC) No. 1907/2006, Article 59(1) or Regulation (EU) 2017/2100 or Regulation (EU) 2018/605.

**Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**SECTION 3: Composition / information on ingredients**

**3.1 Substances**

not applicable

**3.2 Mixtures**

**Description**  
ester oil

**Hazardous ingredients**

CAS No	EC No	Index No	Substance name	Concentration	Classification according to Regulation (EC) No 1272/2008 [CLP]	SCL/ M/ ATE
74-98-6	200-827-9	601-003-00-5	propane	16.9 %	Flam. Gas 1; H220 Press. Gas	
106-97-8	203-448-7	601-004-00-0	butane	16.9 %	Flam. Gas 1; H220 Press. Gas	

**MK-dent PREMIUM SERVICE OIL (LU1011)**

Print date 06.10.2025

Revision date 06.10.2025

Version 1.2 (en)

replaces version of 10.11.2023 (1.1)



**MK-DENT**

CAS No	EC No	Index No	Substance name	Concentration	Classification according to Regulation (EC) No 1272/2008 [CLP]	SCL / M / ATE
75-28-5	200-857-2	601-004-00-0	isobutane	16.9 %	Flam. Gas 1; H220 Press. Gas	
540-84-1	208-759-1	601-009-00-8	2,2,4-trimethylpentane	3.8 %	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	ATE(oral): > 5000 mg/kg ATE(dermal): > 2000 mg/kg ATE(inhalation vapour): > 33.52 mg/L
84082-70-2	282-015-4		peppermint oil	0.45 %	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	

REACH No.	Substance name
01-2119486944-21	propane
01-2119457965-22	2,2,4-trimethylpentane
01-2119974601-36	peppermint oil

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

Remove contaminated, saturated clothing immediately.  
In the event of persistent symptoms receive medical treatment.  
Remove casualty to fresh air and keep warm and at rest.

#### Following inhalation

Remove casualty to fresh air and keep warm and at rest.  
In the event of symptoms refer for medical treatment.

#### Following skin contact

Rinse skin with water.  
In case of irritation consult a doctor.

#### After eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

#### Following ingestion

Do NOT induce vomiting.  
Medical treatment necessary.  
Rinse mouth thoroughly with water.

### 4.2 Most important symptoms and effects, both acute and delayed

No data available

### 4.3 Indication of any immediate medical attention and special treatment needed

#### Notes for the doctor

Treat symptomatically.

**MK-dent PREMIUM SERVICE OIL (LU1011)**

Print date 06.10.2025

Revision date 06.10.2025

Version 1.2 (en)

replaces version of 10.11.2023 (1.1)



**MK-DENT**

---

## **SECTION 5: Firefighting measures**

### **5.1 Extinguishing media**

#### **Suitable extinguishing media**

Dry extinguishing powder

Carbon dioxide (CO<sub>2</sub>)

Water spray jet

#### **Unsuitable extinguishing media**

Full water jet

### **5.2 Special hazards arising from the substance or mixture**

#### **Hazardous combustion products**

Fire gas of organic material has to be classed invariably as respiratory poison.

Nitrogen oxides (NO<sub>x</sub>)

Carbon monoxide

Carbon dioxide (CO<sub>2</sub>)

### **5.3 Advice for firefighters**

#### **Special protective equipment for firefighters**

In case of fire: Wear self-contained breathing apparatus.

Breathing protection and eye protection is required for fire-fighting under presence of fume and vapour

### **Additional information**

Cool endangered containers with water spray and possibly remove them from fire site.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

---

## **SECTION 6: Accidental release measures**

### **6.1 Personal precautions, protective equipment and emergency procedures**

#### **For non-emergency personnel**

Avoid skin and eye contact

Do not inhale gases/vapours/aerosols.

#### **For emergency responders**

Remove persons to safety.

Keep people away and stay on the upwind side.

Personal protection equipment

Remove all sources of ignition.

### **6.2 Environmental precautions**

Do not allow to enter into surface water or drains.

### **6.3 Methods and material for containment and cleaning up**

#### **For containment**

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).

After taking up the material dispose according to regulation.

Ensure adequate ventilation.

### **6.4 Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**MK-dent PREMIUM SERVICE OIL (LU1011)**

Print date 06.10.2025

Revision date 06.10.2025

Version 1.2 (en)

replaces version of 10.11.2023 (1.1)



**MK-DENT**

## **SECTION 7: Handling and storage**

### **7.1 Precautions for safe handling**

#### **Protective measures**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

Do not breathe gas/vapour/aerosol.

Do not get in eyes, on skin, or on clothing.

Usual measures for fire prevention.

Take the usual precautions when handling with chemicals.

#### **Advices on general occupational hygiene**

Please observe work hygiene regulations.

When using do not eat, drink, smoke.

Remove contaminated, saturated clothing immediately.

### **7.2 Conditions for safe storage, including any incompatibilities**

#### **Requirements for storage rooms and vessels**

Keep/Store only in original container.

Container under pressure. Protect from direct sunlight and temperatures above 50°C.

#### **Materials to avoid**

Acid

alkalis

Oxidising agent

#### **Further information on storage conditions**

Keep away from heat and sources of ignition.

### **7.3 Specific end use(s)**

#### **Recommendation**

See section 1.2

## **SECTION 8: Exposure controls/personal protection**

### **8.1 Control parameters**

#### **Occupational exposure limit values**

CAS No	EC No	Substance name	occupational exposure limit value
106-97-8	203-448-7	n-Butane	600 [ml/m3(ppm)] 1450 [mg/m3] Short-term(ml/m3) 750 Short-term(mg/m3) 1810 (UK)
106-97-8	203-448-7	n-Butane	Short-term(ml/m3) 1000 (1) (1) 15 minutes average value (IE)
75-28-5	200-857-2	iso-Butane	Short-term(ml/m3) 1000 (1) (1) 15 minutes average value (IE)

**MK-dent PREMIUM SERVICE OIL (LU1011)**

Print date 06.10.2025

Revision date 06.10.2025

Version 1.2 (en)

replaces version of 10.11.2023 (1.1)



**MK-DENT**

CAS No	EC No	Substance name	occupational exposure limit value
106-97-8	203-448-7	Butane	600 [ml/m3(ppm)] 1450 [mg/m3] Short-term(ml/m3) 750 Short-term(mg/m3) 1810

**DNEL worker**

CAS No	Substance name	DNEL value	DNEL type	Remark
540-84-1	2,2,4-trimethylpentane	773 mg/kg	long-term dermal (systemic)	
540-84-1	2,2,4-trimethylpentane	2035 mg/m <sup>3</sup>	long-term inhalative (systemic)	

**DNEL Consumer**

CAS No	Substance name	DNEL value	DNEL type	Remark
540-84-1	2,2,4-trimethylpentane	699 mg/kg	Long-term – oral, systemic effects	
540-84-1	2,2,4-trimethylpentane	699 mg/kg	long-term dermal (systemic)	
540-84-1	2,2,4-trimethylpentane	608 mg/m <sup>3</sup>	long-term inhalative (systemic)	

## 8.2 Exposure controls

### Appropriate engineering controls

#### Technical measures to prevent exposure

Sufficient ventilation and exhaustion.

### Personal protection equipment

#### Eye/face protection

Eye glasses with side protection

The selected safety goggles must be in compliance with the specifications of EU Directive 89/686/EEC and the resultant standard EN 166.

#### Hand protection

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: Nitrilrubber (index 1)

The protective gloves to be used must comply with the specifications of EC directive 89/686/EEC and the resultant standard EN374.

The exact breakthrough time of the glove material is to be inquired from the protection glove manufacturer and must be strictly adhered to.

#### Body protection:

Protective clothing

#### Respiratory protection

Respiratory protection necessary at:

insufficient exhaust

prolonged exposure

exceeding exposure limit values

Atemschutz nach EN 140 oder EN 136 verwenden: Filter Typ A & P

**MK-dent PREMIUM SERVICE OIL (LU1011)**

Print date 06.10.2025

Revision date 06.10.2025

Version 1.2 (en)

replaces version of 10.11.2023 (1.1)



**MK-DENT**

## **SECTION 9: Physical and chemical properties**

### **9.1 Information on basic physical and chemical properties**

**Physical state**

Aerosol

**Colour**

yellowish

**Odour**

characteristic

**Safety relevant basis data**

	<b>Value</b>	<b>Method</b>	<b>Source, Remark</b>
Odour threshold:			No data available
Melting point/freezing point	not determined		
Boiling point or initial boiling point and boiling range	not determined		
flammability	not determined		
Lower and upper explosion limit	not determined		
Flash point	-80 °C		
Auto-ignition temperature	400 °C		
Decomposition temperature			No decomposition if used as directed.
pH	not determined		
Viscosity	not determined		
Solubility(ies)	Water solubility		practically insoluble
Partition coefficient n-octanol/water (log value)	not determined		
Vapour pressure	not determined		
Density and/or relative density	not determined		
Relative vapour density	not determined		
particle characteristics	not determined		

### **9.2 Other information**

**Other safety characteristics**

	<b>Value</b>	<b>Method</b>	<b>Source, Remark</b>
Explosive properties			Does not apply; nevertheless can be produced explosive vapour/air mixtures

**Other information**

none

**MK-dent PREMIUM SERVICE OIL (LU1011)**

Print date 06.10.2025

Revision date 06.10.2025

Version 1.2 (en)

replaces version of 10.11.2023 (1.1)



**MK-DENT**

## **SECTION 10: Stability and reactivity**

### **10.1 Reactivity**

The product is non-reactive under the recommended storage, use and temperature conditions.

### **10.2 Chemical stability**

The product is chemically stable under recommended conditions of storage, use and temperature.

### **10.3 Possibility of hazardous reactions**

Reactions with strong acids and alkalies.

Reactions with oxidising agents.

### **10.4 Conditions to avoid**

strong heating  
Sunlight

### **10.5 Incompatible materials**

strong acids  
Oxidising agent  
alkalis

### **10.6 Hazardous decomposition products**

No risk of production of decomposition products when appropriately handled and stored.

## **SECTION 11: Toxicological information**

### **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

#### **Acute toxicity**

##### **Animal data**

	Effective dose	Method, Evaluation	Source, Remark
Acute oral toxicity	CAS No540-84-1 2,2,4-trimethylpentane LD50: > 5000 mg/kg Species Rat	OECD 401	
Acute dermal toxicity	CAS No540-84-1 2,2,4-trimethylpentane LD50: > 2000 mg/kg Species Rabbit	OECD 402	
Acute inhalation toxicity	CAS No540-84-1 2,2,4-trimethylpentane Acute inhalation toxicity (vapour) LC50: > 33.52 mg/L Species Rat Exposure time 4 h	OECD 403	

#### **Assessment/classification**

Based on available data, the classification criteria are not met.

#### **Skin corrosion/irritation**

**MK-dent PREMIUM SERVICE OIL (LU1011)**

Print date 06.10.2025

Revision date 06.10.2025

Version 1.2 (en)

replaces version of 10.11.2023 (1.1)



**MK-DENT**

**Animal data**

Result / Evaluation	Method	Source, Remark
slightly irritant but not relevant for classification.		

**Assessment/classification**

Based on available data, the classification criteria are not met.

**Serious eye damage/irritation**

**Animal data**

Result / Evaluation	Method	Source, Remark
slightly irritant but not relevant for classification.		

**Assessment/classification**

Based on available data, the classification criteria are not met.

**Sensitisation to the respiratory tract**

**Assessment/classification**

Based on available data, the classification criteria are not met.

**Skin sensitisation**

**Assessment/classification**

Based on available data, the classification criteria are not met.

**Germ cell mutagenicity**

not determined

**Carcinogenicity**

not determined

**Reproductive toxicity**

not determined

**Overall Assessment on CMR properties**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

**STOT SE 1 and 2**

**Other information**

none

**Assessment/classification**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

**Other information**

none

**Assessment/classification**

Based on available data, the classification criteria are not met.

**MK-dent PREMIUM SERVICE OIL (LU1011)**

Print date 06.10.2025  
Revision date 06.10.2025  
Version 1.2 (en)  
replaces version of 10.11.2023 (1.1)



**MK-DENT**

**Aspiration hazard**

**Assessment/classification**

Based on available data, the classification criteria are not met.

**11.2 Information on other hazards**

**Information on other hazards**

	Effective dose	Method,Evaluation	Source, Remark
Endocrine disrupting properties			No data available

**Other information**

Other hazardous properties may not be excluded.

The product is to be handled with the caution usual with chemicals.

**SECTION 12: Ecological information**

**12.1 Toxicity**

**Aquatic toxicity**

	Effective dose	Method,Evaluation	Source, Remark
Acute (short-term) fish toxicity	CAS No540-84-1 2,2,4-trimethylpentane LC50: 18.4 mg/L Species Oncorhynchus mykiss (Rainbow trout) Test duration 4 d	OECD 203	
	CAS No106-97-8 butane LC50: 24.11 mg/L Species fish Test duration 96 h	QSAR	
	CAS No75-28-5 isobutane LC50: 24.11- 147.6 mg/L Species fish Test duration 96 h	calculated	
	CAS No540-84-1 2,2,4-trimethylpentane NOEC 0.82 mg/L Species Oncorhynchus mykiss (Rainbow trout) Test duration 28 d	QSAR	
Chronic (long-term) fish toxicity	not determined		
Acute (short-term) toxicity to crustacea	CAS No540-84-1 2,2,4-trimethylpentane EC50 0.4 mg/L Species Daphnia magna (Big water flea) Test duration 2 d	QSAR	
	CAS No106-97-8 butane LC50 14.22 mg/L Species Daphnia magna (Big water flea) Test duration 48 h	QSAR	

**MK-dent PREMIUM SERVICE OIL (LU1011)**

Print date 06.10.2025

Revision date 06.10.2025

Version 1.2 (en)

replaces version of 10.11.2023 (1.1)



**MK-DENT**

	Effective dose	Method, Evaluation	Source, Remark
Chronic (long-term) toxicity to aquatic invertebrate	CAS No75-28-5 isobutane LC50 7.02- 69.43 mg/L Species Daphnia magna (Big water flea) Test duration 48 h	calculated	
Acute (short-term) toxicity to algae and cyanobacteria	CAS No540-84-1 2,2,4-trimethylpentane NOEC 0.17 mg/L Species Daphnia magna (Big water flea) Test duration 21 d	OECD 211	
Chronic (long-term) toxicity to aquatic algae and cyanobacteria	not determined		
Toxicity to other aquatic plants/organisms	CAS No540-84-1 2,2,4-trimethylpentane NOEC 0.658 mg/L Species Green algae (Pseudokirchnerella subcapitata) Test duration 3 d	QSAR	
Toxicity to microorganisms	CAS No106-97-8 butane EC50 7.71 mg/L Species Algae Test duration 96 h	QSAR	
	CAS No75-28-5 isobutane EC50 7.71- 16.5 mg/L Species Algae Test duration 96 h	calculated	
	not determined		
	not determined		
			No data available.

**Assessment/classification**

Toxic to aquatic life with long lasting effects.

**12.2 Persistence and degradability**

	Value	Method	Source, Remark
Biodegradation	Degradation rate 22.4		2,2,4-Trimethylpentane Moderately/partially biodegradable.

**12.3 Bioaccumulative potential**

No data available

**12.4 Mobility in soil**

No data available

**12.5 Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**MK-dent PREMIUM SERVICE OIL (LU1011)**

Print date 06.10.2025  
Revision date 06.10.2025  
Version 1.2 (en)  
replaces version of 10.11.2023 (1.1)



**MK-DENT**

**12.6 Endocrine disrupting properties**

	Effective dose	Method, Evaluation	Source, Remark
Endocrine disrupting properties			No data available

**12.7 Other adverse effects**

**Additional ecotoxicological information**

**Additional information**

Do not allow uncontrolled discharge of product into the environment.

**SECTION 13: Disposal considerations**

**13.1 Waste treatment methods**

**Waste codes/waste designations according to EWC/AVV**

Waste code product	Waste name
150104	metallic packaging

**Appropriate disposal / Product**

Consult the appropriate local waste disposal expert about waste disposal.  
Dispose of waste according to applicable legislation.

**Appropriate disposal / Package**

Dispose of in accordance with legal regulations.  
Handle contaminated packages in the same way as the substance itself.

**Remark**

The waste code must be allocated in compliance with the EAK-regulation referring to the specific process and the sector.

The classification of waste is always the responsibility of the end user.

**SECTION 14: Transport information**

	Land transport (ADR/RID)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
<b>14.1 UN number or ID number</b>	UN 1950	UN 1950	UN 1950
<b>14.2 UN proper shipping name</b>	AEROSOLS	AEROSOLS (2,2,4-trimethylpentane)	Aerosols, flammable
<b>14.3 Transport hazard class(es)</b>	2.1	2.1	2.1
<b>14.4 Packing group</b>	-	-	-
<b>14.5 Environmental hazards</b>	ENVIRONMENTALLY HAZARDOUS	ENVIRONMENTALLY HAZARDOUS Marine pollutant	ENVIRONMENTALLY HAZARDOUS

**14.6 Special precautions for user**

No data available

**14.7 Maritime transport in bulk according to IMO instruments**

not applicable

**MK-dent PREMIUM SERVICE OIL (LU1011)**

Print date 06.10.2025

Revision date 06.10.2025

Version 1.2 (en)

replaces version of 10.11.2023 (1.1)



**MK-DENT**

**Land transport (ADR/RID)**

UN number or ID number	UN 1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	2.1
Hazard label(s)	2.1
Classification code	5F
Packing group	-
Environmental hazards	ENVIRONMENTALLY HAZARDOUS
Limited quantity (LQ)	1 L
Special provisions	190, 327, 344, 625
Tunnel restriction code	D

**Sea transport (IMDG)**

UN number or ID number	UN 1950
UN proper shipping name	AEROSOLS (2,2,4-trimethylpentane)
Transport hazard class(es)	2.1
Packing group	-
Environmental hazards	ENVIRONMENTALLY HAZARDOUS
Limited quantity (LQ)	1 L
Marine pollutant	Yes.
EmS	F-D, S-U

**Air transport (ICAO-TI / IATA-DGR)**

UN number or ID number	UN 1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	2.1
Packing group	-
Environmental hazards	ENVIRONMENTALLY HAZARDOUS

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU legislation**

**Authorisations**

None of the components is listed.

**Restrictions on use**

None of the components is listed.

**Other regulations (EU)**

**To follow:**

Aerosol directive (75/324/EEC)

**MK-dent PREMIUM SERVICE OIL (LU1011)**

Print date 06.10.2025  
Revision date 06.10.2025  
Version 1.2 (en)  
replaces version of 10.11.2023 (1.1)



## 15.2 Chemical Safety Assessment

### National regulations

A material safety assessment was not conducted.

## SECTION 16: Other information

### Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Aerosol 1: Aerosols, Category 1

Aquatic Chronic 2: Long-term (chronic) aquatic hazard, Category 2

### Key literature references and sources for data

Data sheets of the sub-supplier.

GESTIS Substance data base (<http://www.hvbg.de/d/bia/fac/zesp/zesp.htm>)

ECHA (European Chemical Agency)

### Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

The product is to be produced on the basis of the available hazard data of the ingredients, as defined in the classification criteria for mixtures for each hazard class in Annex I to Regulation (EC) No 1272/2008, classified.

Classification method:

Calculation

Test data

### Additional information

National and local regulations concerning chemicals shall be observed.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products.

In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Each user is responsible for the implementation of the national special regulations.

### Relevant H- and EUH-phrases (Number and full text)

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.